



DIMPLED MEMBRANE OR DAMPPROOF TO LOCAL BUILDING CODE

FREE DRAINING GRANULAR FILL C/W WEeping TILE

ENGINEERED WOOD FLOOR
SEE ARCHITECTURAL PLANS

SILL PLATE C/W ANCHOR BOLTS AS PER LOCAL BUILDING CODE

6" MIN.

2% SLOPE

2-10M IN TOP OF WALL TYPICAL

1/2" GYPSUM BOARD

VERTICAL REBAR PLACED TO THE INSIDE FACE OF WALL (SEE REINFORCING TABLE)

2 5/8" TYPICAL

DOWELS PER D.1.8

REFER TO LOCAL BUILDING CODES FOR FOOTING SIZES

NOTES:

1. DETAIL TO BE USED IN CONJUNCTION WITH ADVANTAGE ICF SYSTEM TECHNICAL & INSTALLATION MANUAL.
2. HORIZONTAL AND VERTICAL REBAR OVERLAP TO BE 450 mm (18") FOR 10M AND 650 mm (26") FOR 15M.

No.	REVISION DESCRIPTION	DATE	BY	CHKD	APPD



PLANT OR PROJECT	8" ADVANTAGE ICF SYSTEM	SCALE	NTS
DESIGN	G DOREN	DATE	JULY, 09
DRAWN	L XIE	DATE	JULY, 09
CHECKED	J WHALEN	DATE	JULY, 09
DRAWING No.	S.3.8	REV.	